

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A robust customizable computing system comprising:
a processing control unit having a non-peripheral based encasement and an electrical printed circuit board configuration that comprises multiple interconnected boards;
an external object; and
means for operably connecting said processing control unit to said external object, said processing control unit introducing intelligence into said external object and causing said external object to perform smart functions.

2. (Currently Amended) The robust customizable computer processing system of claim 1, wherein said processing control unit further comprises:
~~an the non-peripheral based encasement module~~ comprising:
a main support chassis having a plurality of wall supports and a plurality of
junction centers containing means for supporting a computer component therein;
a dynamic back plane that provides support for connecting peripheral and other computing components directly to a system bus without requiring an interface;
means for enclosing said main support chassis and providing access to an interior portion of said non-peripheral based encasement ~~module~~;
one or more computer processing components disposed within said junction centers of said non-peripheral based encasement ~~module~~; and
means for cooling said interior portion of said non-peripheral based encasement ~~module~~.

3. (Original) The robust customizable computing system of claim 1, wherein said means for operably connecting comprises means for physically coupling said processing control unit to said external object, such that said processing control unit functions as a load bearing component.

4. (Original) The robust customizable computing system of claim 1, further comprising at least one other processing control unit operably connected to said external object.

5. (Original) The robust customizable computing system of claim 1, wherein said processing control unit comprises a load bearing structure.

6. (Currently Amended) The robust customizable computing system of claim 1, wherein said means for operably connecting comprises a direct connection via a universal port formed in a dynamic back plane ~~on of said non-peripheral based encasement~~ processing control unit.

7. (Currently Amended) The robust customizable computing system of claim 1, wherein said means for operably connecting comprises a wired connection that connects to a port ~~formed within of~~ of said processing control unit.

8. (Original) The robust customizable computing system of claim 1, wherein said means for operably connecting comprises a wireless connection.

9. (Currently Amended) The robust customizable computing system of claim 1, wherein said means for operably connecting comprises means for engaging ~~an~~the external object.

10. (Currently Amended) The robust customizable computing system of claim 9, wherein said means for engaging an external object comprises a slide receiver formed on said processing control unit that functions to receive a matching insert located on ~~an~~the external object.

11. (Original) The robust customizable computing system of claim 1, wherein said external object is selected from the group consisting of any object, system, device, apparatus, component, structure, component of a structure, item of manufacture, and inanimate object.

12. (Original) The robust customizable computing system of claim 9, wherein said external object comprises a workstation computer having snap-on peripheral devices that operably connect to said processing control unit.

13. (Original) The robust customizable computing system of claim 1, wherein said external object comprises circuitry, such that said processing control unit operably connects to said circuitry.

14. (Currently Amended) The robust customizable computing system of claim 1, wherein said electrical printed circuit board configuration of said processing control unit is a tri-board~~is non-peripheral based~~.

15. (Currently Amended) A robust customizable computing system comprising:
- an external object;
- a processing control unit having a non-peripheral based encasement and an electrical printed circuit board configuration that comprises multiple interconnected boards, wherein the processing control unit is configured to physically supporting said external object or a component of said external object; and
- means for operably connecting said processing control unit to said external object, said processing control unit introducing intelligence into said external object and causing said external object to perform smart functions.

16. (Currently Amended) A method for introducing intelligence into an external object and enabling smart functions therein, said method comprising:
- obtaining an external object;
 - operably connecting a processing control unit to said external object, said processing control unit having a non-peripheral based encasement and an electrical printed circuit board configuration that comprises multiple interconnected boards; and
 - initiating one or more computing functions within said processing control unit to cause said external object to perform smart functions.
17. (Currently Amended) The method of claim 16, wherein said ~~processing control unit comprises~~:
- ~~a non-peripherals-based encasement module comprising~~ comprises:
 - a main support chassis for providing main support to said non-peripheral based encasement module;
 - one or more plates removably coupled to said main support chassis for providing access to an interior portion of said non-peripheral based encasement module;
 - one or more processing components removably disposed within said non-peripheral based encasement module; and
 - means for cooling said non-peripheral based encasement module and dissipating heat to the surrounding ambient air.

18. (Currently Amended) The non-peripherals computer processing system of claim 17, wherein said encasement is substantially cubical in shape, such that said encasement module comprises:

a main support chassis having first, second and third side wall supports;

first and second end plates removably coupled to said main support chassis and

comprising a plurality of ventilation ports;

a dynamic back plane removably coupled to said main support chassis; and

a tri-board electrical printed circuit board configuration removably secured within said encasement module.